

# SPIROTECH SPECIFICATION SHEET



Product: SpiroTrap 28 mm Compression fitting

Type:

UE028WJ

Date:

11/19/2019

Customer:

Project:

Reference:

## Design criteria

|                     |                          |                   |
|---------------------|--------------------------|-------------------|
| Medium:             | Water / glycol (max 50%) |                   |
| Max. flow velocity: | 1                        | m/s               |
| Max. flow rate:     | 2.00                     | m <sup>3</sup> /h |
| Max. pressure:      | 6                        | bar-g             |
| Max. temperature:   | 110                      | °C                |
| Design standard:    | EN 13445                 |                   |


## Testing and quality assurance

|                                           |     |
|-------------------------------------------|-----|
| Leakage test:                             | no  |
| Test certificate:                         | no  |
| Design and manufacturing acc. 2014/68/EU: | yes |
| Material certificates (structural parts): | no  |
| Drawing:                                  | no  |

## Construction materials

|                   |            |
|-------------------|------------|
| Body:             | Brass      |
| Swivel:           | Brass      |
| Drain valve:      | Brass      |
| Spirotube Tube:   | Copper     |
| Spirotube Wire:   | Copper     |
| Spirotube Solder: | Tin(SnCu3) |
| Magnet:           | Neodymium  |

## Drawing



## Dimensions

|     |         |
|-----|---------|
| d:  | 28 mm   |
| h:  | 117 mm  |
| Hh: | 149 mm  |
| Hv: | 177 mm  |
| h1: | 32 mm   |
| L:  | 112 mm  |
| D:  | 84 mm   |
| B:  | 149 mm  |
| b:  | 127 mm  |
| x:  | >110 mm |
| y:  | >50 mm  |
| e:  | G3/4    |

Volume 0.39 ltr

Dry weight (approx) 2.3 kg

Subject to changes